



A SUPERIOR ENERGY SERVICES COMPANY

INTERNATIONAL SNUBBING SERVICES					
HWO / Snubbing Unit - Typical Specifications					
	150k	225k	340k	460k	600k
Unit Type	Stand Alone & Quick Rig	Stand Alone & Quick Rig	Stand Alone & Quick Rig	Stand Alone	Stand Alone
Pull Capacity	150,000 lb	225,000 lb	340,000 lb	460,000 lb	600,000 lb
Push (Snub) Capacity	78,000 lb.	120,000 lb	170,000 lb	230,000 lb	300,000 lb
Rotary Torque	6,000 ft-lb	6,000 ft-lb	22,500 ft-lb	22,500 ft-lb	22,500 ft-lb
Jack Stroke Length	10 feet	10 feet	10 feet	10 feet	10 feet
Thru Bore	Up to 7-1/16"	7-1/16"	13-5/8" Window Thru bore up to 21"	13-5/8" Window Thru bore up to 21"	13-5/8" Window Thru bore up to 21"
Stipping BOP (Snubbing)	Up to 7-1/16"	Up to 7 1/16"	Up to 13-5/8"	Up to 21 1/4"	Up to 21 1/4"
Work Window Size	6ft - 10ft	6ft - 10ft	6 ft - 12 ft	6 ft - 12 ft	6 ft - 12 ft
Pipe Size	3/4" - 3 1/2"	3/4" - 5 1/2"	2 3/8" - 7 5/8"	2 3/8" - 10 3/4"	2 3/8" - 10-3/4"
Power Slips	225,000 lb	225,000 lb	340,000 lb	460,000 lb	600,000 lb
Power Tongs	4 1/2" Standard	4 1/2" Standard	5 1/2" UHT	5 1/2" UHT - 8 5/8" UHT	5 1/2" UHT - 8 5/8" UHT
Gin Pole Winch	2 x 1,500 lb	2 x 1,500 lb	2x 2,500 lb, 1 x 10,000 lb	2x 2,500 lb, 1 x 10,000 lb	2x 2,500 lb, 1 x 10,000 lb
Rated Working Pressure (Surface PSI)	20,000 psi	20,000 psi	20,000 psi	20,000 psi	20,000 psi